QX3LR SOUNDBAR



3"2-WAY SHALLOW DEPTH IN-WALL STERED SOUNDBAR



Size 7.269 h x Custom w x 3.875 d (in) 184.5 h x 991 w x 98 d (mm)

Freq Response 70Hz-24kHz±3dB

Impedance 4/8 ohms (Config. Dependent)

Sensitivity 89dB 2.83V /1m Power req. 25-150W/Channel

Woofer (4) 3" (76mm) High Excursion Tweeter (8) 0.75" (19mm) Aluminum Finishes White Paintable Grille

(Paintable by Request Only)

PCB OX3LRPB PCBF OX3LRPBF

2185 Park Place, Minden, NV 89423 Ph:+1.775.461.7500 www.jamesloudspeaker.com

(4) 3" (76mm) High Excursion Aluminum Driver (8) 0.75" (19mm) Aluminum Dome Tweeters in Quad-Arrays

The QX3LR speaker raises the bar of home entertainment systems, setting new levels in sound output and wide frequency response. The stereo format of this bar features two individual systems to provide both left and right channels for full stereo sound in a single enclosure. Perfect for any home entertainment system, this versatile SoundBar can be custom built to match each individual TV, providing seamless integration and elegant design as well as high quality audio. Equipped with high output, low-profile woofers and the signature ultra-wide dispersion QX style quad aluminum tweeter array, this low-visibility SoundBar packs a powerful punch in a small package. Capable of reaching frequencies across a broad range down to below 70Hz, the QX3LR offers full range response with an impressive 89dB sensitivity.

The cabinet design features all aircraft grade aluminum for strength, sonic performance, and suitability for outdoor/marine applications. Complete with a matching borderless stainless steel perforated grille which sits only 3/16" (5mm) off the wall or completely flush with the addition of a pre-construction board, this speaker is both sturdy and reliable, and can be elegantly integrated into each system, providing a subdued visual effect, designed to be as unobtrusive as possible. Matching in-wall surrounds are available as well, model numbers QX320 and QX330.

For outdoor/marine applications, order the QX3LRM.

NOTE: When ordering flush mount pre-construction boards (PBF models), you must specify the thickness of the sheetrock that you will be using (1/2", 5/8" etc). This is a suffix to the part number and added to the end.



Proud Grille Look (Requires PCB)

20190611