SONANCE VISUAL EXPERIENCE DATA SHEET

VX66R

TECHNICAL SPECIFICATIONS

SKU	VX66R 96014 - Pair
Tweeter	1" (25mm) ceramic dome, Ferrofluid-cooled, acoustic back chamber
Woofer	6.5" (165mm) Kevlar/ Nomex cone, rubber surround, pivoting
Dispersion Technology	Sinusoidal textured waveguide
Speaker Pivot	Coincident Woofer + Tweeter Pivoting
Frequency Response	43Hz - 20kHz +/-3dB
Impedance	8 ohms nominal; 6 ohms minimum
Power Handling (RMS)	5 watts minimum; 140 watts maximum
Sensitivity (2.83V/1m)	90dB SPL
Mounting Technology	Flex Frame 1 or 2-stage, 4 x RotoLock® Clamps
Round Micro Trim Grille (Dia)	9.62" (244.4mm)
Round Trimless Grille (Dia)	9.28" (235.6mm)
Square Micro Trim Grill (WxH)	9.62" x 9.62" (244.4mm x 244.4mm)
Square Trimless Grille (WxH)	9.28" x 9.28" (235.6mm x 235.6mm)
Speaker Mounting Depth (D)	4.92" (125mm)
Mounting Depth + Retrofit Encl.	5.75" (146.1mm)
Cut-Out Dims (Dia)	8.25" (210mm)
Shipping Weight	9 lbs. (4.1kg)


DIMENSIONAL DRAWINGS



Cut-Out Diameter **Front View**



Mounting Depth (Open Back) **Side View**



Mounting Depth + Retrofit Enclosure **Side View**

VX 6" ROUND ACCESSORIES

6" Micro Trim Round Grille / Pair 935	5/5
VX6R-GRILLE-NT	
6" Trimless Round Grille / Pair 935	576
VX6SQ-T	
6" Micro Trim Square Adapter / Pair 960)30
VX6SQ-T-5PR	
6" Micro Trim Square Adapter / 5xPair 960)33
VX6SQ-NT	
6" Trimless Square Adapter / Pair 935	686
VX6SQ-NT-5PR	
6" Trimless Square Adapter / 5xPair 935	89
VX6-ENCL-R	
6" Round Enclosure / Pair 963	43
FLEXBRK-6-R	
6" Round Flex Bracket / 5x Pair 923	37

LIMITED LIFETIME WARRANTY

Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the life of the Product, except for the grille, which is warranted for five (5) years. Sonance will at its option and expense either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. ©2024 Sonance. All rights reserved. Sonance product specification information visit our website at www.sonance.com. 991 Calle Amanecer • San Clemente, CA 92673 USA • Phone: (949) 492-7777 • Fax: (949) 361-5151 • Technical Support: (949) 492-7777 01.16.2024