# SONANCE

## VISUAL EXPERIENCE DATA SHEET

#### VX62R

#### TECHNICAL SPECIFICATIONS

VX62R

96012 - Pair SKU

1" (25mm) cloth dome, Ferrofluid-cooled, **Tweeter** 

acoustic back chamber

Woofer 6.5" (165mm) textured polypropylene cone,

rubber surround, pivoting

**Dispersion Technology** Sinusoidal textured waveguide

**Speaker Pivot** Coincident Woofer + Tweeter Pivoting

45Hz - 20kHz +/-3dB Frequency Response

8 ohms nominal; 6 ohms minimum Impedance

5 watts minimum; 125 watts maximum Power Handling (RMS)

89dB SPL Sensitivity (2.83V/1m)

Flex Frame 1 or 2-stage, 4 x RotoLock® Clamps **Mounting Technology** 

9.62" (244.4mm) Round Micro Trim Grille (Dia) 9.28" (235.6mm) Round Trimless Grille (Dia)

9.62" x 9.62" (244.4mm x 244.4mm) Square Micro Trim Grill (WxH) 9.28" x 9.28" (235.6mm x 235.6mm) Square Trimless Grille (WxH)

4.92" (125mm) Speaker Mounting Depth (D) 5.75" (146.1mm) Mounting Depth + Retrofit Encl. 8.25" (210mm) Cut-Out Dims (Dia) 9 lbs. (4.1kg) **Shipping Weight** 

#### DIMENSIONAL DRAWINGS



Cut-Out Diameter **Front View** 



Mounting Depth (Open Back)

Side View



Mounting Depth + Retrofit Enclosure

Side View

### VX 6" ROUND ACCESSORIES

VX6R-GRILLE-T 6" Micro Orline Normal Grille / Pair	93575
VX6R-GRILLE-NT 6" Trimless Round Grille / Pair VX6SQ-T	93576
6" Micro Trim Square Adapter / Pair VX6SQ-T-5PR	96030
6" Micro Trim Square Adapter / 5xPair VX6SQ-NT	96033
6" Trimless Square Adapter / Pair VX6SQ-NT-5PR	93586
6" Trimless Square Adapter / 5xPair VX6-ENCL-R	93589
6" Round Enclosure / Pair FLEXBRK-6-R	96343
6" Round Flex Bracket / 5x Pair	92337

#### LIMITED LIFETIME WARRANTY