SONANCE

VISUAL EXPERIENCE DATA SHEET

VX82

TECHNICAL SPECIFICATIONS

VX82

SKU 96006 - Pair

Tweeter 1.2" (30mm) cloth dome, Ferrofluid-

cooled, acoustic back chamber

Woofer 8" (203mm) textured polypropylene

cone, rubber surround

Dispersion Technology Sinusoidal textured waveguide

Frequency Response 38Hz - 20kHz +/-3dB

Impedance 8 ohms nominal; 6 ohms minimum

Power Handling (RMS) 5 watts minimum; 125 watts maximum

Sensitivity (2.83V/1m) 90dB SPL

Mounting Technology Flex Frame 1- or 2-stage,

6 RotoLock® Clamps

Micro Trim Grille (WxH) 9.72" x 15.87" (246.8mm x 403.1mm)

Trimless Grille (WxH) 9.37" x 15.52" (238.0mm x 394.3mm)

Speaker Mounting Depth (D) 3.64" (92.4mm)

Mounting Depth + Retrofit Encl. 3.86" (98.1mm)


Cut-Out Dims (WxH) 8.5" x 14.5" (216mm x 368mm)

Shipping Weight 20 lbs. (9kg)

DIMENSIONAL DRAWINGS




Cut-Out Width Front View



Mounting Depth (Open Back)

Side View



Mounting Depth + Retrofit Enclosure

Side View

VX 8" RECTANGLE ACCESSORIES

VX8-GRILLE-T

8" Micro Trim Rectangle Grille / Pair 93583

VX8-GRILLE-NT

8" Trimless Rectangle Grille / Pair 93584

VX8-ENCL

8" Rectangle Enclosure / Pair 96242

FLEXBRK-8

8" Rectangle Flex Bracket / 5x Pair 92246

LIMITED LIFETIME WARRANTY