



VISUAL EXPERIENCE with QUADRATECH DATA SHEET



8.25" (210mm) Cut-Out Diameter **Front View**



3.8" (96.4mm) Mounting Depth (Open Back) **Side View**



3.92" (99.6mm) Shallow Enclosure Side View



5.92" (150.4mm) Deep Enclosure Side View

VXQ68R TECHNICAL SPECIFICATIONS

VXQ68R SKU 66056 - Each

Tweeter 0.75" (19mm) four titanium domes, Ferrofluid-cooled, acoustic back chamber

Woofer 6.5" (165mm) Aluminum cone, Santoprene

surround

Dispersion Technology Quadratech Tweeter with Cymatic Diffuser

40Hz - 20kHz +/-3dB Frequency Response

8 ohms nominal; 6 ohms minimum **Impedance** Power Handling (RMS) 5 watts minimum; 150 watts maximum

Sensitivity (2.83V/1m) 90dB SPL

Mounting Technology 1-stage, 4 x RotoLock® Clamps

Round Micro Trim Grille (Dia) 9.64" (244.8mm) Round Trimless Grille (Dia) 9.28" (235.6mm)

Square Micro Trim Grille (WxH) 9.64" x 9.64" (244.8mm x 244.8mm) Square Trimless Grille (WxH) 9.28" x 9.28" (235.6mm x 235.6mm)

Speaker Mounting Depth (D) 3.8" (96.4mm) Mounting Depth + Shallow Encl. 3.92" (99.6mm) Mounting Depth + Deep Encl. 5.92" (150.4mm) Cut-Out Dims (WxH) 8.25" (210mm) Shipping Weight 10 lbs. (4.5kg)

VXQ 6" ROUND ACCESSORIES

VXQ6R-GRILLE-T

VXQ6-SE-R 6" XPC Micro Trim Round Grille / Each 6" Round Shallow Enclosure / Each 60477

60478

VXQ6-DE-R

VXQ6R-GRILLE-NT 6" XPC Trimless Round Grille / Each

6" Round Deep Enclosure / Each

60469

60468

VXQ6SQ-T

6" XPC Micro Trim Square Adapter / Each 60489

FLEXBRK-6-R

6" Round Flex Bracket / 5x Pair

6" XPC Trimless Square Adapter / Each 60490

LIMITED FIVE (5) YEAR WARRANTY Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual

©2024 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com