

M40T		
Specifications.	Values	Notes / Comments.
Nominal system impedance	4 ohm	(Z-min 4.6 ohm)
Frequency response	100-20Khz	(average response in room +/- 2dB)
Frequency roll off	100 Hz	( -6dB at 100 Hz near field wall mounted)
Crossover frequency	2.0 Khz	"Phase focused" (4th&2nd order)
Front Tweeter (shielded)	1" Dome	Coated silk dome / Neodymium magnet
Front Woofer (shielded)	4"	Coated glass fibre
Side drivers (shielded)	2 x 3"	Polymer coated Textured Paper
Power handling	80 watt	Long term IEC-268-5 (cycled input 100-20Khz)
Power handling	50 watt	Rated IEC-268-5 (constant input 100-20Khz)
Recommended amp power	25-125 watt	(Recommended amp power to drive speaker)
Sensitivity	85 dB	Average SPL 2.83V / 1mtr (on axis 200-10KHz)
System princip		Sealed enclosure
Connection	Terminal gold plating	Screw for 5 mm cable / Banana
Accessories	Yes	Wall mount brackets/screws/gloves
Welcome card	Yes	"Included in packing"
Finish		Black / White satin
Dimensions	H x W x D	7.7 x 7,8 x 4,8 inch-19.5x20x 12,2 cm (incl grill)
Weight		6.5 lb / 2.9 kg
Version 1. August 2019		