

<b>MP300</b>		
<b>Specifications.</b>	<b>Values</b>	<b>Notes / Comments.</b>
Nominal system impedance	4 ohm	(Z-min 3.6 ohm)
Frequency response	80-22Khz	(average response in room +/- 3dB)
Frequency roll off	80 Hz	(-6db 80 Hz near field)
Crossover frequency	1.5Khz	"Phase focused" (4th/2nd order)
Integrated Tweeter array shielded	3 x 1" Dome	High excursion / soft dome / Low compression
Woofer	2 x 6.5"	Coated glass fibre
Power handling	325 watt	Long term IEC-268-5 (cycled input 60-20Khz)
Power handling	125 watt	Rated IEC-268-5 (constant input 60-20Khz)
Recommended amp power	25-500 watt	Recommended amp power min / max
Sensitivity	92 dB	Average SPL 2.83 volt/1mtr (on axis 200-10KHz)
Max SPL Continued	112 dB	Sine wave 100-8000 Hz / THD < 10%
Max SPL Peak	116 dB	Sine wave 100-8000 Hz / THD < 10%
System princip		Sealed enclosure
Connection	Terminal gold plating	Screw for 6 mm cable / Banana
Accessories	Yes	"Mounting screws & gloves" Rubber feets
Buyer's certificate	Yes	"Included in packing"
Certification THX	Yes	THX Ultra 2 Certified
Calibration disc	Yes	"Included in Left speaker packing"
Finish	Paint	Black Satin & White Satin
Dimensions top	H x W x D	15.5 x 13.4 x 6,3 inch - 39.5 x 34 x 16 cm
Dimensions bottom	H x W x D	15,5 x 13,4 x 4,7 inch - 39,5 x 34 x 12 cm
Weight	Netto	26 lbs / 12 kg
	Version 3. May 2017	